



Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Issue date: 15/08/2025

Revision date: 15/08/2025

Supersedes: 05/04/2023

Version: 3.0

SECTION 1: Identification

1.1. GHS Product identifier

Product form	Article
Name	Li-Ion Battery 16S3P ANR26650 for FX 3-A tool
UN-No. (ADR)	3480
Product code	BU Direct Fastening

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture	For professional use only Electrical batteries and accumulators
------------------------------	--

1.4. Supplier's details

Supplier

Hilti Qatar W.L.L.
Souq Al Rawda
Salwa Road
P.O. Box 24097
QA Doha Ad Dawḥah
Qatar
T +974 4406 3600, F +974 4406 3669
QA.info@hilti.com

Department issuing data specification sheet

Hilti AG
Feldkircherstraße 100
FL 9494 Schaan
Liechtenstein
T +423 234 2111
product.compliance-direct.fastening@hilti.com

1.5. Emergency phone number

Emergency number	Emergency CONTACT (24-Hour-Number): GBK GmbH Global Regulatory Compliance +49 (0)6132-84463 +974 4406 3600
------------------	---

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. GHS Label elements, including precautionary statements

Labelling according to the United Nations GHS

No labelling applicable

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification For the battery chemical materials are stored in a hermetically sealed metal case, designed to withstand Temperatures and pressures encountered during normal use. As a result, during normal use there is no physical danger of ignition or explosion and chemical danger of hazardous materials leakage.

It may cause heat generation or electrolyte leakage if battery terminals contact with other metals. Electrolyte is flammable. In case of electrolyte leakage move the battery from fire immediately.

However if exposed to a fire, added mechanical shocks, decomposed, added electric stress by miss-use, the gas release vent will be operated. The battery case will be broken at the extreme, hazardous materials may be released.

Moreover, if heated strongly by a surrounding fire, acrid gas may be emitted.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments Lithium Ion rechargeable battery pack:
Name/Type Energy content (Wh)
16S3P ANR26650 396
This product contains a positive electrode (Lithium iron phosphate), a negative electrode (graphite), electrolyte and binder.

The physical form of the product, however, precludes exposure to workers under normal conditions of use.

This mixture does not contain any substances to be mentioned according to the applicable regulations

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	If the electrolyte is leaking out of the battery pack, the following measures have to be taken.
First-aid measures after inhalation	Allow affected person to breathe fresh air. Allow the victim to rest. If necessary seek medical advice.
First-aid measures after skin contact	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects	Not expected to present a significant hazard under anticipated conditions of normal use.
Potential adverse human health effects and symptoms	This product contains an organic electrolyte. If the electrolyte is leaking out of the battery pack, the following effects are known when getting into contact: Irritation: severely irritant to eyes. Severely irritant to skin. Irritation: may cause irritation to the respiratory system.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media Cool batteries and accumulators with water jet. In case of fire in the surroundings: Use extinguishing agent suitable for surrounding fire.

5.2. Specific hazards arising from the chemical

Fire hazard Water may not extinguish burning batteries but will cool adjacent batteries and control the spread of fire. Burning batteries will burn themselves out. Virtually all fires involving lithium batteries can be controlled by flooding with water. However, the contents of the battery will react with water and form hydrogen gas. In a confined space, hydrogen gas can form an explosive mixture. In this situation, smothering agents are recommended.

Hazardous decomposition products in case of fire Formation of toxic gases is possible during heating or in case of fire. Water might react with released Lithium hexafluorophosphate to highly toxic gaseous hydrogen fluoride.

5.3. Special protective actions for fire-fighters

Firefighting instructions Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting Use a self-contained breathing apparatus and also a protective suit.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures No flames, no sparks. Eliminate all sources of ignition. Isolate from fire, if possible, without unnecessary risk. For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

6.1.1. For non-emergency personnel

Emergency procedures Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment Equip cleanup crew with proper protection.

Emergency procedures Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up Take up liquid spill into absorbent material.

Other information Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling Do not soak in water or seawater.
Do not expose to strong oxidizers.
Do not give a strong mechanical shock or fling.
Never disassemble, modify or deform.
Do not connect the positive terminal to the negative terminal with electrically conductive material.
Use only the chargers / electric tools specified by Hilti to charge or discharge the battery.

Do not throw into fire or expose to high temperatures (>85 °C).
Do not connect the positive terminal to the negative terminal with electrically conductive material. Charge within limits of 0°C to 45°C temperature.
Discharge within limits of -20°C to +60°C temperature.
Always wash hands after handling the product.

Hygiene measures

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Additional hazards when processed

Normal use of this product shall imply use in accordance with the instructions on the packaging and in line with the expectations of a professional user.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Protect from heat and direct sunlight. Protect from moisture.

Storage area

Store in a well-ventilated place.

Incompatible products

Strong bases. Strong acids.

Incompatible materials

Sources of ignition. Direct sunlight.

Information on mixed storage

Store away from water.

Do not store together with electrically conductive materials.

The accu-pack should be stored at 30 to 50% of the charging capacity.

Avoid storing in places where it is exposed to static electricity.

Storage temperature

-20 – 45 °C (humidity: 0% - 80%)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

Ensure adequate ventilation. If the electrolyte is leaking out of the battery pack, the following measures have to be taken.

Other information

Do not eat, drink or smoke when using this product.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection

Wear protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12		EN ISO 374

Eye protection

Chemical goggles or safety glasses

Respiratory protection

No additional information available

Personal protective equipment symbol(s)



8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state

Solid

Colour

Grey.

Odour

Not available

Odour threshold

Not available

Melting point

Not available

Freezing point

Not applicable

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

Boiling point	Not available
Flammability	Non flammable.
Lower explosion limit	Not applicable
Upper explosion limit	Not applicable
Flash point	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
pH	Not available
pH solution	Not available
Viscosity, kinematic (calculated value) (40 °C)	Not applicable
Partition coefficient n-octanol/water (Log Kow)	Not available
Vapour pressure	Not available
Vapour pressure at 50°C	Not available
Density	Not available
Relative density	Not available
Relative vapour density at 20°C	Not applicable
Solubility	Not available
Particle size	Not available

9.2. Data relevant with regard to physical hazard classes (supplemental)

Explosive limits	Not applicable
Explosive properties	Risk of explosion by shock, friction, fire or other sources of ignition.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Heating may cause a fire or explosion.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Water, humidity.

10.5. Incompatible materials

Conductive materials, water, seawater, strong oxidizers and strong acids.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	Not classified (Based on available data, the classification criteria are not met)
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitization	Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	Not classified (Based on available data, the classification criteria are not met)

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

STOT-repeated exposure Not classified (Based on available data, the classification criteria are not met)
 Aspiration hazard Not classified (Based on available data, the classification criteria are not met)

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool	
Viscosity, kinematic	Not applicable
Potential adverse human health effects and symptoms	This product contains an organic electrolyte. If the electrolyte is leaking out of the battery pack, the following effects are known when getting into contact: Irritation: severely irritant to eyes. Severely irritant to skin. Irritation: may cause irritation to the respiratory system.
Other information	When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) Not classified (Based on available data, the classification criteria are not met) (Based on available data, the classification criteria are not met)
 Hazardous to the aquatic environment, long-term (chronic) Not classified (Based on available data, the classification criteria are not met) (Based on available data, the classification criteria are not met)

12.2. Persistence and degradability

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool	
Bioaccumulative potential	No additional information available

12.4. Mobility in soil

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool	
Mobility in soil	No additional information available

12.5. Other adverse effects

Ozone Not classified (Based on available data, the classification criteria are not met)
 Other adverse effects No additional information available
 Other information Do not allow battery packs to penetrate the soil.
 The battery cell may corrode and electrolyte may leak.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations Dispose in a safe manner in accordance with local/national regulations. Refer to manufacturer/supplier for information on recovery/recycling.
 Ecological waste information Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3480	UN 3480	UN 3480	UN 3480	UN 3480

Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

ADR	IMDG	IATA	ADN	RID
14.2. UN proper shipping name				
LITHIUM ION BATTERIES	LITHIUM ION BATTERIES	Lithium ion batteries	LITHIUM ION BATTERIES	LITHIUM ION BATTERIES
Transport document description				
UN 3480 LITHIUM ION BATTERIES, 9, (E)	UN 3480 LITHIUM ION BATTERIES, 9	UN 3480 Lithium ion batteries, 9	UN 3480 LITHIUM ION BATTERIES, 9	UN 3480 LITHIUM ION BATTERIES, 9
14.3. Transport hazard class(es)				
9	9	9	9	9
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	M4
Special provisions (ADR)	230, 310, 348, 376, 377, 387, 636
Limited quantities (ADR)	0
Excepted quantities (ADR)	E0
Packing instructions (ADR)	P903, P908, P909, P910, P911, LP903, LP904, LP905, LP906
Transport category (ADR)	2
Tunnel restriction code (ADR)	E

Transport by sea

Special provisions (IMDG)	188, 230, 310, 348, 376, 377, 384, 387
Limited quantities (IMDG)	0
Excepted quantities (IMDG)	E0
Packing instructions (IMDG)	P903, P908, P909, P910, P911, LP903, LP904, LP905, LP906
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-I
Stowage category (IMDG)	A
Stowage and handling (IMDG)	SW19
Flash point (IMDG)	
Properties and observations (IMDG)	Electrical batteries containing lithium ion may react (e.g. flame, heat, emission of toxic, corrosive or flammable gases or vapours) or disassemble due to damage, defects or short circuit.

Air transport

PCA Excepted quantities (IATA)	E0
PCA Limited quantities (IATA)	Forbidden
PCA limited quantity max net quantity (IATA)	Forbidden
PCA packing instructions (IATA)	Forbidden



Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

PCA max net quantity (IATA)	Forbidden
CAO packing instructions (IATA)	See 965
CAO max net quantity (IATA)	See 965
Special provisions (IATA)	A88, A99, A154, A183, A201, A213, A331, A334, A802
ERG code (IATA)	12FZ

Inland waterway transport

Classification code (ADN)	M4
Special provisions (ADN)	188, 230, 310, 348, 376, 377, 387, 636, 677
Limited quantities (ADN)	0
Excepted quantities (ADN)	E0
Equipment required (ADN)	PP
Number of blue cones/lights (ADN)	0

Rail transport

Classification code (RID)	M4
Special provisions (RID)	188, 230, 310, 348, _376, 377, 387, 636, 677
Limited quantities (RID)	0
Excepted quantities (RID)	E0
Packing instructions (RID)	P903, 908, 909, P910, P911, LP903, LP904, LP905, LP906
Transport category (RID)	2
Colis express (express parcels) (RID)	CE2
Hazard identification number (RID)	90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Regulatory reference Not listed on the United States TSCA (Toxic Substances Control Act) inventory.

SECTION 16: Other information

Issue date	8/15/2025
Revision date	8/15/2025
Supersedes	4/5/2023

Section	Changed item	Comments
1	Trade name	Modified
14	Transport information	Modified

Abbreviations and acronyms

CAS-No. - Chemical Abstract Service number
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE - Acute Toxicity Estimate
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL - Derived-No Effect Level
EC50 - Median effective concentration
ED - Endocrine disruptor
EC-No. - European Community number



Li-Ion Battery 16S3P ANR26650 for FX 3-A tool

Safety Data Sheet

according to the United Nations GHS (Rev. 10, 2023)

EN - European Standard
IATA - International Air Transport Association
IMDG - International Maritime Dangerous Goods
IOELV - Indicative Occupational Exposure Limit Value
LC50 - Median lethal concentration
LD50 - Median lethal dose
NOEC - No-Observed Effect Concentration
OECD - Organisation for Economic Co-operation and Development
N.O.S. - Not Otherwise Specified
OEL - Occupational Exposure Limit
PBT - Persistent Bioaccumulative Toxic
PNEC - Predicted No-Effect Concentration
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS - Safety Data Sheet
STP - Sewage treatment plant
TLM - Median Tolerance Limit
TRGS - Technical Rules for Hazardous Substances
VOC - Volatile Organic Compounds
WGK - Water Hazard Class
vPvB - Very Persistent and Very Bioaccumulative
NOAEL - No-Observed Adverse Effect Level
NOAEC - No-Observed Adverse Effect Concentration
LOAEL - Lowest Observed Adverse Effect Level

Other information

A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis.

SDS UN HILTI

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.